

INPUT

110 volts or 220 volts D.C.

DATA

Battery Outfit	Battery		Amp. hour Capacity (20 hr. rate)	Duplicate or Single	Nominal Battery Voltage	Charging Current (amps.)	Charging Resistance Patt. No.	Charge/Discharge Board Patt. No.	Installation Spec.	Establishment List
	Patt. No.	No. fitted								
BB1	W1469A	4	130	Duplicate	12	15	* W6926	W6927	B704	E570
BBm	W1469A	8	130	Duplicate	24	15	* W6916	W6927	B704	E570
BBn	W1469A	4	130	Single	24	15	* W6926	W6927	B704	E570
BBp	W1469A	8	130	Duplicate	24	15	M457	M456	B402	E712
BBu	W3433A	1	40	Single	12	4.5	W3216	-	B704	E715
BBw	W3433A	2	40	Single	24	4.5	W3216	-	B704	E715
BBy	7541	12	250	Single	24	30	-	56776	B704	E775
BBz with Type 60EQR	W1469A	8	130	Duplicate	24	15	* W6926	-	B495	E876
	7541	4	220	Duplicate	4	44	* 7241A	W6427		
BCe	14143	3	45	Single	24	12.5	* W6926	66151	B704	E965
BCf	7541	12	250	Single	24	40	-	14184	B704	E993
BCg	W1469A	4	130	Single	24	15	-	14185	B704	E993
Type 86M Battery Outfit	W1469A	# 4	130	Single	24	15	+ 7241AA	-	B342	E604

\* Two fitted in 220 volt D.C. Ships  
 † Four fitted in 220 volt D.C. Ships

# 8 in 2 single batteries when supplying 2 sets in same office.

WEIGHTS

Batteries		Charging Resistances		Charge/Discharge Board		Motor Generators (for BBy)	
Patt. No.	lb.	Patt. No.	lb.	Patt. No.	lb.	Patt. No.	lb.
7541	62	W3216	15	W6927	12	54317(110V)	280
14143	44	W6926	25	56776	120	54318(220V)	282
W1469A	66	M457	10	66151	31		
W3433	44			M456	10		
				14184	350		
				14185	200		

BATTERY OUTFITS  
SUMMARY OF DATA

BATT.